



10/3 L5-20 CABLE

| PART NUMBER | LENGTH | WEIGHT |
|-------------------|---------------|---------|
| 1400-03-14-01-001 | 100' | 30 lbs. |
| 1400-03-14-02-001 | 75' | 23 lbs. |
| 1400-03-14-03-001 | 50' | 16 lbs. |
| 1400-03-14-04-001 | 25' | 8 lbs. |
| 1400-03-14-06-001 | 5' | 2 lbs. |
| 1400-03-14-07-001 | 10' | 4 lbs. |
| 1400-03-14-08-001 | 125' | 37 lbs. |
| 1400-03-14-09-001 | 150' | 45 lbs. |
| 1400-03-14-10-001 | 200' | 59 lbs. |
| 1400-03-14-99-001 | Custom Length | TBD |

CABLE ASSEMBLY SPECIFICATIONS

| | |
|--------------------------|--|
| CONNECTOR | Hubbell Brand, 125VAC 30A 1PH, Nylon, Black and White, Connector HBL2313, Plug HBL2311, UL/CSA |
| STRAIN RELIEF | Insulgrip Connector Bodies |
| CABLE | 10/3 TYPE SOOW 600V 90°C UL Listed, 30 Amps |
| ASSEMBLY AMPACITY | 20 Amps |

Cables have a 6" length of clear heatshrink installed on each end to allow the end user to activate over any labels or information applied to the cable.