

DESCRIPTION	Non-Breakered Stringer Box, 19 Pin I/O X 6 Duplex Edison, With Truss Mount.
Dimensions	17" Overall Length, 3.875" Over Width, 4.625" Overall Height
Weight	4.9lbs
Input Voltage	120 VAC 60Hz, Six Circuits @ 20A
Thru	Unswitched Thru Connector
Output Voltage	6 Circuits, 120VAC, 60 Hz, 20A
Construction	Shell Made from Boltaron 4335 Extruded Acrylic PVC Alloy Sheet, UL94 V-0 Rating, ¼" Thick, Panels are .090 Aluminum, Black Anodized, Diamond Bit Engraving, NEMA 1
Breakers	None
Listing	ETL Listed. Conforms to UL STD 1640, UL STD 508A, Certified to CAN/CSA STD C22.2 No 14

CONNECTOR SPECIFICATIONS

CONNECTOR SPECIFICATIONS		
CONNECTORS, I/O	CEEP Brand, Circular Style, 419AR, 19Pin, 25A, 400VAC. Socapex and VSC Compatible, Aluminum Alloy, Black Finish, UL	
CONNECTORS, OUTPUT	Hubbell Brand, NEMA 5-20, Edison Duplex, HBL 5352 BLK	
FEATURES	Cheeseborough 2" Truss Mount Clamp	





1.800.227.6784 FOR MORE INFORMATION http://www.motionlabs.com/