

DESCRIPTION	Non-Breakered Stringer Box, 19 Pin I/O X 6 Stage Pin. With Truss Mount
Dimensions	17" Overall Length, 3.875" Over Width, 4.625" Overall Height
Weight	4.9lbs
Input Voltage	120 VAC 60Hz, Six Circuits @ 20A
Thru	Unswitched Thru Connector
Output Voltage	6 Circuits, 120VAC, 60 Hz, 20A
Construction	Shell Made from Boltaron 4335 Extruded Acrylic PVC Alloy Sheet, UL94 V-0 Rating, 1/4" Thick. Panels are .090 Aluminum, Black Anodized, Diamond Bit Engraving, NEMA 1
Breakers	None
Listing	ETL Listed. Conforms to UL STD 1640, UL STD 508A, Certified to CAN/CSA STD C22.2 No 14

CONNECTOR SPECIFICATIONS

CONNECTORS, I/O	CEEP Brand, Circular Style, 419AR, 19Pin, 25A, 400VAC. Socapex and VSC Compatible, Aluminum Alloy, Black Finish, UL
CONNECTORS, OUTPUT	Marinco Brand, 20FR, Stage Pin, 125VAC, 20A, Black, UL
FEATURES	Cheeseborough 2" Truss Mount Clamp





1.800.227.6784 FOR MORE INFORMATION http://www.motionlabs.com/