



12/3 L5-20 CABLE

| PART NUMBER | LENGTH | WEIGHT |
|-------------------|---------------|---------|
| 1400-03-10-01-002 | 100' | 24 lbs. |
| 1400-03-10-02-002 | 75' | 18 lbs. |
| 1400-03-10-03-002 | 50' | 12 lbs. |
| 1400-03-10-04-002 | 25' | 7 lbs. |
| 1400-03-10-06-002 | 5' | 2 lbs. |
| 1400-03-10-07-002 | 10' | 3 lbs. |
| 1400-03-10-08-002 | 125' | 29 lbs. |
| 1400-03-10-09-002 | 150' | 35 lbs. |
| 1400-03-10-10-002 | 200' | 46 lbs. |
| 1400-03-10-99-002 | Custom Length | TBD |

CABLE ASSEMBLY SPECIFICATIONS

| | |
|--------------------------|--|
| CONNECTOR | Hubbell Brand, 125VAC 20A 1PH, Nylon, Black and White, Connector HBL2313, Plug HBL2311, UL/CSA |
| STRAIN RELIEF | Insulgrip Connector Bodies |
| CABLE | 12/3 TYPE SOOW 600V 90°C UL Listed, 25 Amps |
| ASSEMBLY AMPACITY | 20 Amps |

Cables have a 6" length of clear heatshrink installed on each end to allow the end user to activate over any labels or information applied to the cable.