

DESCRIPTION	100A Inline Disconnect, MXF, 10Ka
Dimensions	23" Overall Length, 12" Over Width, 10.5" Overall Height
Weight	34lbs
Voltage	120/208Y VAC 3Phase 60Hz
Breaker Type	Square D Brand Q Frame, 3 Pole, UL Listed, CSA Certified, IEC Rated
Breaker Ratings	100 Amperes, 240VAC, 10Ka Interrupt Rating.
Construction	Covers Made from Boltaron 4335 Extruded Acrylic PVC Alloy Sheet, UL94 V-0 Rating, ¼" Thick. Panels are .125 Aluminum, Black Anodized, Diamond Bit Engraving, NEMA 1
Listing	ETL Listed. Conforms to UL STD 1640, UL STD 508A, Certified to CAN/CSA STD C22.2 No 14

CONNECTOR SPECIFICATIONS

CONNECTORS, I/O	Marinco Brand, Cam Tech Device, 400A/600V, 16 Series, 5 Colors, UL/CSA
FEATURES	Blue LED Indicators on Line and Load side of Breaker, Aluminum Anodized and Color coded doors on Output Phases. (Neutral and Ground Doors available)
OPTIONS	25Ka, 65Ka or 100Ka Current Interrupt ratings available. Reverse Ground and/or Neutral connector configurations available



