



16/7 Dual Twist Hoist Power/Control Cable L16-20 Power ~ L14-20 Control

PART NUMBER	LENGTH	WEIGHT
1400-04-30-01-001	100'	25 lbs.
1400-04-30-02-001	75'	20 lbs.
1400-04-30-03-001	50'	15 lbs.
1400-04-30-04-001	25'	10 lbs.
1400-04-30-06-001	5'	6 lbs.
1400-04-30-07-001	10'	7 lbs.
1400-04-30-08-001	125'	30 lbs.
1400-04-30-09-001	150'	35 lbs.
1400-04-30-10-001	200'	45 lbs.
1400-04-30-99-001	Custom Length	TBD

CABLE ASSEMBLY SPECIFICATIONS

CONNECTORS HOIST SIDE	Hubbell Brand, Nylon, Black and White, Power Connector, 480VAC 20A 3PH, HBL2433, Control Plug, 125/250VAC 20A, HBL2411, UL/CSA
CONNECTORS DISTRO SIDE	Hubbell Brand, Nylon, Black and White, Power Plug, 480VAC 20A 3PH, HBL2431, Control Connector, 125/250VAC 20A, HBL2413, UL/CSA
CABLE	16/7 TYPE SEOOOW 600V 105°C UL/CSA Listed, 13 Amps
ASSEMBLY AMPACITY	13 Amps

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable. A strain relief clip is provided on the hoist end of cable.