



8/4 L16-30 CABLE

| PART NUMBER | LENGTH | WEIGHT |
|-------------------|---------------|----------|
| 1400-03-48-01-003 | 100' | 68 lbs. |
| 1400-03-48-02-003 | 75' | 51 lbs. |
| 1400-03-48-03-003 | 50' | 35 lbs. |
| 1400-03-48-04-003 | 25' | 18 lbs. |
| 1400-03-48-06-003 | 5' | 4 lbs. |
| 1400-03-48-07-003 | 10' | 8 lbs. |
| 1400-03-48-08-003 | 125' | 85 lbs. |
| 1400-03-48-09-003 | 150' | 102 lbs. |
| 1400-03-48-10-003 | 200' | 135 lbs. |
| 1400-03-48-99-003 | Custom Length | TBD |

CABLE ASSEMBLY SPECIFICATIONS

| | |
|--------------------------|--|
| CONNECTOR | Hubbell Brand, 480VAC 30A, 3PH Nylon, Black and White. Connector HBL2733, Plug HBL2731, UL/CSA |
| STRAIN RELIEF | Insulgrip Connector Bodies |
| CABLE | 8/4 TYPE SOOW 600V 90°C UL Listed, 35 Amps |
| ASSEMBLY AMPACITY | 30 Amps |

Cables have a 6" length of clear heatshrink installed on each end to allow the end user to activate over any labels or information applied to the cable.