



Encoder / Loadcell Data Cable

PART NUMBER	LENGTH	WEIGHT
1400-06-37-01-001	100'	8 lbs.
1400-06-37-02-001	75'	6 lbs.
1400-06-37-03-001	50'	4 lbs.
1400-06-37-04-001	25'	2 lbs.
1400-06-37-06-001	5'	1/2 lbs.
1400-06-37-07-001	10'	1 lbs.
1400-06-37-08-001	125'	10 lbs.
1400-06-37-09-001	150'	12 lbs.
1400-06-37-10-001	200'	16 lbs.
1400-06-37-99-001	Custom Length	TBD

CABLE ASSEMBLY SPECIFICATIONS

CONNECTOR	Neutrik, 6 Pole Connector, Nickel housing, Solder, Silver Contacts, 7.5A
BACKSHELL	Zinc Diecast Nickel Shell
STRAIN RELIEF	Polyuretan Boot, Polyacetal Strain Relief
CABLE	22gauge / 6 conductor, 3Twisted Pair w/Foil Wrap, Braid and Drain Wire, PVC Jacket, Pairs are Yellow/Green, Brown/White and Pink/Grey

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable.