

DESCRIPTION	Non-Breakered Stringer Box, L21-30 I/O X 3 L6-30 With Truss Mount.
Dimensions	15.5" Overall Length, 3.875" Over Width, 4.625" Overall Height
Weight	5.5lbs
Input Voltage	120/208Y VAC 3Phase 60Hz, 30A
Thru	Unswitched Thru Connector
Output Voltage	3 Circuits, 250VAC, Single Phase 60 Hz, 30A
Construction	Shell Made from Boltaron 4335 Extruded Acrylic PVC Alloy Sheet, UL94 V-0 Rating, 1/4" Thick, Panels are .090 Aluminum, Black Anodized, Diamond Bit Engraving, NEMA 1
Breakers	None
Listing	ETL Listed. Conforms to UL STD 1640, UL STD 508A, Certified to CAN/CSA STD C22.2 No 14

## **CONNECTOR SPECIFICATIONS**

CONNECTORS, I/O	Hubbell Brand, NEMA L21-30 30A 3PH, Nylon, White. Inlet,
	HBL2815, Thru Outlet, HBL2816. UL/CSA
CONNECTORS, OUTPUT	Hubbell Brand NEMA L6-30 30A, HBL2626. UL/CSA
FEATURES	Cheeseborough 2" Truss Mount Clamp



