PART NUMBER 1150-02-151-408-0002



DESCRIPTION	Non-Breakered Stringer Box, 19 Pin I/O X 6 Powercon. With Truss Mount.
Dimensions	17" Overall Length, 3.875" Over Width, 4.625" Overall Height
Weight	5.5lbs
Input Voltage	120 VAC 60Hz, Six Circuits @ 20A
Thru	Unswitched Thru Connector
Output Voltage	6 Circuits, 120VAC, 60 Hz, 20A
Construction	Shell Made from Boltaron 4335 Extruded Acrylic PVC Alloy Sheet, UL94 V-0 Rating, ¼" Thick, Panels are .090 Aluminum, Black Anodized, Diamond Bit Engraving, NEMA 1
Breakers	None
Listing	ETL Listed. Conforms to UL STD 1640, UL STD 508A, Certified to CAN/CSA STD C22.2 No 14

CONNECTOR SPECIFICATIONS

CONNECTORS, I/O	CEEP Brand, Circular Style, 419AR, 19Pin, 25A, 400VAC. Socapex and VSC Compatible, Aluminum Alloy, Black Finish, UL
CONNECTORS,	Neutrik Brand, NAC3MP8, Powercon, 250VAC, 20A, White,
OUTPUT	UL, CUL, VDE, SEV
FEATURES	Cheeseborough 2" Truss Mount Clamp



