



### 12/7 Dual Twist Hoist Power/Control Cable L5-20 Power ~ L14-20 Control

PART NUMBER	LENGTH	WEIGHT
1400-04-13-01-500	100'	47 lbs.
1400-04-13-02-500	75'	36 lbs.
1400-04-13-03-500	50'	26 lbs.
1400-04-13-04-500	25'	15 lbs.
1400-04-13-06-500	5'	7 lbs.
1400-04-13-07-500	10'	9 lbs.
1400-04-13-08-500	125'	57 lbs.
1400-04-13-09-500	150'	67 lbs.
1400-04-13-10-500	200'	88 lbs.
1400-04-13-99-500	Custom Length	TBD

#### CABLE ASSEMBLY SPECIFICATIONS

<b>CONNECTORS HOIST SIDE</b>	Hubbell Brand, Nylon, Black and White, Power Connector, 125VAC 20A 1PH, HBL2313, Control Plug, 125/250VAC 20A, HBL2411, UL/CSA
<b>CONNECTORS DISTRO SIDE</b>	Hubbell Brand, Nylon, Black and White, Power Plug, 125VAC 20A 1PH, HBL2311, Control Connector, 125/250VAC 20A, HBL2413, UL/CSA
<b>CABLE</b>	12/7 TYPE SEOOOW 600V 105°C UL/CSA Listed, 25 Amps
<b>ASSEMBLY AMPACITY</b>	20 Amps

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable. A strain relief clip is provided on the hoist end of cable.