



### 14/7 Dual Twist Hoist Power/Control Cable L6-20 Power ~ L14-20 Control

PART NUMBER	LENGTH	WEIGHT
1400-04-43-01-524	100'	43 lbs.
1400-04-43-02-524	75'	33 lbs.
1400-04-43-03-524	50'	24 lbs.
1400-04-43-04-524	25'	14 lbs.
1400-04-43-06-524	5'	7 lbs.
1400-04-43-07-524	10'	9 lbs.
1400-04-43-08-524	125'	52 lbs.
1400-04-43-09-524	150'	61 lbs.
1400-04-43-10-524	200'	80 lbs.
1400-04-43-99-524	Custom Length	TBD

#### CABLE ASSEMBLY SPECIFICATIONS

<b>CONNECTORS HOIST SIDE</b>	Hubbell Brand, Nylon, Black and White, Power Connector, 250VAC 20A 1PH, HBL2323, Control Plug, 125/250VAC 20A, HBL2411, UL/CSA
<b>CONNECTORS DISTRO SIDE</b>	Hubbell Brand, Nylon, Black and White, Power Plug, 250VAC 20A 1PH, HBL2321, Control Connector, 125/250VAC 20A, HBL2413, UL/CSA
<b>CABLE</b>	14/7 TYPE SEOOW 600V 105°C UL/CSA Listed, 18 Amps
<b>ASSEMBLY AMPACITY</b>	18 Amps

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable. A strain relief clip is provided on the hoist end of cable.