



16/7 Dual Twist Hoist Power/Control Cable L15-20 Power ~ L14-20 Control

PART NUMBER	LENGTH	WEIGHT
1400-04-30-01-014	100'	25 lbs.
1400-04-30-02-014	75'	20 lbs.
1400-04-30-03-014	50'	15 lbs.
1400-04-30-04-014	25'	10 lbs.
1400-04-30-06-014	5'	6 lbs.
1400-04-30-07-014	10'	7 lbs.
1400-04-30-08-014	125'	30 lbs.
1400-04-30-09-014	150'	35 lbs.
1400-04-30-10-014	200'	45 lbs.
1400-04-30-99-014	Custom Length	TBD

CABLE ASSEMBLY SPECIFICATIONS

CONNECTORS HOIST SIDE	Hubbell Brand, Nylon, Black and White, Power Connector, 250VAC 20A 3PH, HBL2423, Control Plug, 125/250VAC 20A, HBL2411, UL/CSA
CONNECTORS DISTRO SIDE	Hubbell Brand, Nylon, Black and White, Power Plug, 250VAC 20A 3PH, HBL2421, Control Connector, 125/250VAC 20A, HBL2413, UL/CSA
CABLE	16/7 TYPE SEOOOW 600V 105°C UL/CSA Listed, 13 Amps
ASSEMBLY AMPACITY	13 Amps

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable. A strain relief clip is provided on the hoist end of cable.