



16/7 Hoist Power/Control Cable Multi-Pin Circular Style 7Pin

PART NUMBER	LENGTH	WEIGHT
1400-02-30-01-001	100'	22 lbs.
1400-02-30-02-001	75'	17 lbs.
1400-02-30-03-001	50'	12 lbs.
1400-02-30-04-001	25'	7 lbs.
1400-02-30-06-001	5'	3 lbs.
1400-02-30-07-001	10'	4 lbs.
1400-02-30-08-001	125'	27 lbs.
1400-02-30-09-001	150'	32 lbs.
1400-02-30-10-001	200'	42 lbs.
1400-02-30-99-001	Custom Length	TBD

CABLE ASSEMBLY SPECIFICATIONS

CONNECTOR	Various Brand, Multi-Pin, Circular Series, 7Pin, Solder, 25A, Black, UL Listed
BACKSHELL STRAIN RELIEF	Delrin, PG16, Liquid Tight Straight Strain Relief Fitting, Flex Nut, Nylon, Black, PG-16, Cable Range 9mm - 16mm
CABLE	16/7 TYPE SEOOW 600V 105°C UL/CSA Listed, 13 Amps
ASSEMBLY AMPACITY	13 Amps

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable. A strain relief clip is provided on the hoist end of cable.