



16/7 Hoist Power/Control Cable Multi-Pin 1/4 Turn Bayonet Style 7Pin

PART NUMBER	LENGTH	WEIGHT
1400-05-30-01-002	100'	22 lbs.
1400-05-30-02-002	75'	17 lbs.
1400-05-30-03-002	50'	12 lbs.
1400-05-30-04-002	25'	7 lbs.
1400-05-30-06-002	5'	3 lbs.
1400-05-30-07-002	10'	4 lbs.
1400-05-30-08-002	125'	27 lbs.
1400-05-30-09-002	150'	32 lbs.
1400-05-30-10-002	200'	42 lbs.
1400-05-30-99-002	Custom Length	TBD

CABLE ASSEMBLY SPECIFICATIONS

CONNECTOR	Various Brand, Multi-Pin, 1/4 Turn, Bayonet Style 7Pin, Shell Size 20, Aluminum, Black, Crimp, 23A
BACKSHELL STRAIN RELIEF	Delrin, PG16, Liquid Tight Straight Strain Relief Fitting, Flex Nut, Nylon, Black, PG-16, Cable Range 9mm - 16mm
CABLE	16/7 TYPE SEOOOW 600V 105°C UL/CSA Listed, 13 Amps
ASSEMBLY AMPACITY	13 Amps

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable. A strain relief clip is provided on the hoist end of cable.