



### L21-30 CABLE, NON UL

PART NUMBER	LENGTH	WEIGHT
1400-03-19-01-001	100'	56 lbs.
1400-03-19-02-001	75'	42 lbs.
1400-03-19-03-001	50'	28 lbs.
1400-03-19-04-001	25'	15 lbs.
1400-03-19-06-001	5'	4 lbs.
1400-03-19-07-001	10'	6 lbs.
1400-03-19-08-001	125'	69 lbs.
1400-03-19-09-001	150'	83 lbs.
1400-03-19-10-001	200'	110 lbs.
1400-03-19-99-001	Custom Length	TBD

#### CABLE ASSEMBLY SPECIFICATIONS

<b>CONNECTOR</b>	Hubbell Brand, 120/208VAC 30A 3PH, Nylon, Black and White, Connector HBL2813, Plug HBL2811, UL/CSA
<b>STRAIN RELIEF</b>	Insulgrip Connector Bodies
<b>CABLE</b>	8/5 TYPE SOOW 600V 90°C Non-UL Listed, 28 Amps
<b>ASSEMBLY AMPACITY</b>	28 Amps

Cables have a 6" length of clear heatshrink installed on each end to allow the end user to activate over any labels or information applied to the cable.


**motionlaboratories**  
 power distribution and motor control systems


**1.800.227.6784** FOR MORE INFORMATION  
<http://www.motionlabs.com/>

520 Furnace Dock Road . Cortlandt Manor, New York 10567 . Phone: (914)788-8877 Fax: (914)788-8866