



P26 Yellow Remote

PART NUMBER	LENGTH	WEIGHT
1400-05-39-01-001	100'	16 lbs.
1400-05-39-02-001	75'	12 lbs.
1400-05-39-03-001	50'	8 lbs.
1400-05-39-04-001	25'	4 lbs.
1400-05-39-06-001	5'	1 lbs.
1400-05-39-07-001	10'	2 lbs.
1400-05-39-08-001	125'	20 lbs.
1400-05-39-09-001	150'	24 lbs.
1400-05-39-10-001	200'	32 lbs.
1400-05-39-99-001	Custom Length	TBD

CABLE ASSEMBLY SPECIFICATIONS

CONNECTOR	Shell, Aluminum Alloy Plating, Olive Green Cadmium, Insulator, Neoprene Elastomer, Crimps, Gold Plated Overall, Inserted and Removed From the Rear, Retained by Metallic Clip. Electrical, 300V RMS, 13A
BACKSHELL	P-26, Multi-Pin UNEF 2B 15/16-20 X PG 11, Delrin
STRAIN RELIEF	Liquid Tight Straight Strain Relief Fitting, Flex Nut, Nylon, Black, PG-11, Cable Range .20"-.39"
CABLE	26 Conductor, 22AWG Stranded Tinned Copper, PVC insulated, unshielded, PVC Jacket Cable, Yellow, 300V RMS, 80C

Cables have a 6" length of clear heat shrink installed on each end to allow the end user to activate over any labels or information applied to the cable.